

TYPE: L

Demension (mm)

L TYPE	Torque		Max. rpm	D	L	L ₁	L ₂	d		GD ² kgf cm ²	(mm) Weight kgf
	Max.	Min.						Min.	Max.		
L-035	0.05	0.15	6000	16.1	20.5	6.5	7.5	4	8	0.1	0.04
L-050	0.15	0.45	4500	27	43.2	15.5	12.2	6	16	1.0	0.14
L-070	0.3	0.9	3600	35	49.2	18.5	12.2	6	20	3.3	0.27
L-075	0.5	1.5	3600	45	54.4	21	12.4	8	26	9.1	0.45
L-090	0.8	2.4	3000	54	55	21	13	10	28	15	0.60
L-095	1	3	3000	55	61	24	13	10	28	17	0.70
L-099	2.0	6.0	3000	66	73	30	18	12	36	42	1.40
L-100	2.5	7.5	3000	66	88	35	18	12	36	43	1.50
L-110	5	15	2500	85	110	44	22	12	48	147	3.00
L-150	10	30	2500	96	118.5	46	26.5	16	48	258	4.00
L-190	15	45	2000	115	138.5	56	26.5	16	58	628	6.90
L-225	20	60	2000	127	152.5	63.5	26.5	18	60	1685	10.45
L-276	25	75	2000	157	200	79	41	22	73	5265	21.36

NOTE: ALL RATING IN THIS CHART ARE BASED ON A NORMAL SERVICE FACTOR OR A SERVICE FACTOR OF 1.

